

- groups-20305** ✓ The value of the attribute **groups:kind** of a **Group** object must conform to the syntax of SBML data type **groupKind** and may only take on the allowed values of **groupKind** defined in SBML; that is, the value must be one of the following: 'classification', 'partonomy' or 'collection'. (Reference: SBML Level 3 Package specification for Groups, Version 1, [Section 3.3 on page 5.](#))
- groups-20306** ✓ The attribute **groups:name** on a **Group** must have a value of data type **string**. (Reference: SBML Level 3 Package specification for Groups, Version 1, [Section 3.3 on page 5.](#))
- groups-20307** ✓ The **ListOfMembers** subobject on a **Group** object is optional, but if present, this container object must not be empty. (Reference: SBML Level 3 Package specification for Groups, Version 1, [Section 3.3 on page 5.](#))
- groups-20308** ✓ Apart from the general notes and annotations subobjects permitted on all SBML objects, a **ListOfMembers** container object may only contain **Member** objects. (Reference: SBML Level 3 Version 1 Core, Section 3.2.)
- groups-20309** ✓ A **ListOfMembers** object may have the optional SBML Level 3 Core attributes **metaid** and **sboTerm**. No other attributes from the SBML Level 3 Core namespaces are permitted on a **ListOfMembers** object. (Reference: SBML Level 3 Version 1 Core, Section 3.2.)
- groups-20310** ✓ A **ListOfMembers** object may have the optional attributes **groups:id** and **groups:name**. No other attributes from the SBML Level 3 Groups namespaces are permitted on a **ListOfMembers** object. (Reference: SBML Level 3 Package specification for Groups, Version 1, [Section 3.4 on page 7.](#))
- groups-20311** ✓ The attribute **groups:name** on a **ListOfMembers** must have a value of data type **string**. (Reference: SBML Level 3 Package specification for Groups, Version 1, [Section 3.4 on page 7.](#))
- groups-20312** ▲ If **ListOfMembers** objects from different **Group** objects contain **Member** elements that reference the same SBase object, the **sboTerm** and any child **Notes** or **Annotation** elements set for those **ListOfMembers** should be consistent, as they all should apply to the same referenced object. (References: SBML Level 3 Package Specification for Groups, Version 1, [Section 3.4 on page 7.](#))
- groups-20313** ✓ Member references may not be circular: no **Member's** **idRef** or **metaIdRef** may reference itself, its parent **ListOfMembers**, nor its parent **Group**. If a **Member** references a **Group** or a **ListOfMembers**, the same restrictions apply to that subgroup's children: they may not reference the **Member**, its parent **ListOfMembers**, nor its parent **Group**, and if any of those children reference a **Group**, the same restrictions apply to them, etc. (Reference: SBML Level 3 Package specification for Groups, Version 1, [Section 3.5.4 on page 8.](#))

Rules for Member object

- groups-20401** ✓ A **Member** object may have the optional SBML Level 3 Core attributes **metaid** and **sboTerm**. No other attributes from the SBML Level 3 Core namespaces are permitted on a **Member**. (Reference: SBML Level 3 Version 1 Core, Section 3.2.)
- groups-20402** ✓ A **Member** object may have the optional SBML Level 3 Core subobjects for notes and annotations. No other elements from the SBML Level 3 Core namespaces are permitted on a **Member**. (Reference: SBML Level 3 Version 1 Core, Section 3.2.)
- groups-20403** ✓ A **Member** object may have the optional attributes **groups:id** and **groups:name** and must have a value for one (and exactly one) of the attributes **groups:idRef** and **groups:metaIdRef**. No other attributes from the SBML Level 3 Groups namespaces are permitted on a **Member** object. (Reference: SBML Level 3 Package specification for Groups, Version 1, [Section 3.5 on page 7.](#))

- groups-20404** ✓ The attribute `groups:name` on a **Member** must have a value of data type `string`. (Reference: SBML Level 3 Package specification for Groups, Version 1, [Section 3.5 on page 7.](#))
- groups-20405** ✓ The value of the attribute `groups:idRef` of a **Member** object must be the identifier of an existing **SBase** object defined in the enclosing **Model** object. (Reference: SBML Level 3 Package specification for Groups, Version 1, [Section 3.5 on page 7.](#))
- groups-20406** ✓ The value of the attribute `groups:metaIdRef` of a **Member** object must be the `metaid` of an existing **SBase** object defined in the enclosing **Model** object. (Reference: SBML Level 3 Package specification for Groups, Version 1, [Section 3.5 on page 7.](#))
- groups-20407** ✓ The value of a `groups:idRef` attribute on **Member** objects must conform to the syntax of the SBML data type `SIdRef`. (References: SBML Level 3 Package Specification for Groups, Version 1, [Section 3.5 on page 7.](#))
- groups-20408** ✓ The value of a `groups:metaIdRef` attribute on **Member** objects must conform to the syntax of the SBML data type `IDREF`. (References: SBML Level 3 Package Specification for Groups, Version 1, [Section 3.5 on page 7.](#))

1
2
3
4
5
6
7
8
9
10
11
12
13
14

Acknowledgments

1
2
3
4
5
6
7
8
9
Work such as this does not take place in a vacuum; many people contributed ideas and discussions that shaped the Groups proposal that you see before you. We particularly thank Nicolas Le Novère, Frank Bergmann, Sarah Keating, Allyson Lister, Robert Phair, Sven Sahle, Stefan Hoops, Chris Myers, and the members of the *sbml-discuss* and *sbml-groups* mailing lists for suggestions and comments.

We would also like to thank Andreas Dräeger, Ben Heavner, Brett Olivier, Kieran Smallbone, and Anna Zhukova for their work in implementing 'Groups' support in their own software tools, with Brett in particular investigating implementaton of the 'nested groups' aspect of the specification.

This work was funded by the National Institutes of Health (USA) under grant R01 GM070923.

References

- Anwar, N., Demir, E., Hucka, M., and Novère, N. L. (2011). HARMONY 2011: The HACKathon on Resources for MODELING in biology. Available via the World Wide Web at http://www.co.mbine.org/events/HARMONY_2011.
- Eriksson, H.-E. and Penker, M. (1998). *UML Toolkit*. John Wiley & Sons, New York.
- Finney, A. (2004). Multicomponent Species: A proposal for SBML Level 3. Available via the World Wide Web at <http://sbml.org/images/1/19/20041015-finney-multicomponent.pdf>.
- Finney, A., Hucka, M., and Novère, N. L. (2006). The Systems Biology Markup Language (SBML) Level 2: Structures and Facilities for Model Definitions. Available via the World Wide Web at <http://sbml.org/Documents/Specifications>.
- Hucka, M. (2006). Groups proposal (2009-09). Available via the World Wide Web at http://sbml.org/Community/Wiki/SBML_Level_3_Proposals/Groups_Proposal_%282009-09%29.
- Hucka, M. (2012). Groups proposal updated (2012-06). Available via the World Wide Web at http://sbml.org/Community/Wiki/SBML_Level_3_Proposals/Groups_Proposal_Updated_%282012-06%29.
- Juty, N., Novère, N. L., Taddeo, L., and Hucka, M. (2009). Seventh SBML Hackathon. Available via the World Wide Web at http://sbml.org/Events/Hackathons/The_7th_SBML_Hackathon.
- Kutmon, M., Evelo, C., Bader, G., Novère, N. L., and Hucka, M. (2012). HARMONY 2012: The HACKathon on Resources for MODELING in biology. Available via the World Wide Web at http://www.co.mbine.org/events/HARMONY_2012.
- Oestereich, B. (1999). *Developing Software with UML: Object-Oriented Analysis and Design in Practice*. Addison-Wesley.
- SBML Editors, T. (2006a). Results of L2v2 specification vote #8: Introducing CompartmentType. Available via the World Wide Web at <http://sbml.org/Forums/index.php?t=tree&goto=3057&rid=2>.
- SBML Editors, T. (2006b). Results of L2v2 specification vote #9: Introducing Generalized Reactions. Available via the World Wide Web at <http://sbml.org/Forums/index.php?t=tree&th=764&mid=5567&rid=2>.
- SBML Team (2010). The SBML issue tracker. Available via the World Wide Web at <http://sbml.org/issue-tracker>.